

# "AB"

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
20 November 2003 (20.11.2003)

PCT

(10) International Publication Number  
**WO 03/096485 A1**

(51) International Patent Classification<sup>7</sup>: **H01R 12/16**

(21) International Application Number: PCT/US03/14410

(22) International Filing Date: 9 May 2003 (09.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/379,950 10 May 2002 (10.05.2002) US

(71) Applicant: **MOLEX INCORPORATED** [US/US]; 2222  
Wellington Court, Lisle, IL 60532 (US).

(72) Inventors: **REGNIER, Kent, E.**; 541 South Grace Street,  
Lombard, IL 60148 (US). **BANAKIS, Emanuel, G.**;  
1460 North Webster Street, Naperville, IL 60563 (US).  
**CASHER, Patrick, R.**; 409 Pinecreek Drive, North  
Aurora, IL 60542 (US).

(74) Agent: **PAULIUS, Thomas, D.**; Molex Incorporated,  
2222 Wellington Court, Lisle, IL 60532 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU,  
ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **EDGE CARD CONNECTOR ASSEMBLY WITH TUNED IMPEDANCE TERMINALS**



(57) Abstract: A surface mount connector has a dielectric housing with first and second opposing mating faces. The first mating face includes first terminals and the second mating face includes second terminals. The first and second terminals each have a tail portion, a contact portion and a terminal retention portion. The terminal retention portion engages the connector housing, and an opening, or hole, is formed in the retention section of the terminal. This opening is sized to keep sufficient metal remaining to retain the terminal in the housing, yet having sufficient surface area to provide a desired capacitance and/or inductance for tuning the impedance of the terminal to the preselected level, the second terminals each having a second terminal retention section with a central portion removed thereof, the removed central portion being spaced away from the first terminal retention area, while minimizing the surface area, size and shape of the central section for tuning the

impedance of the terminal to a preselected range.

WO 03/096485 A1

## **EDGE CARD CONNECTOR ASSEMBLY WITH TUNED IMPEDANCE TERMINALS**

### **Background of the Invention**

The present invention is directed generally to edge card connectors and, more specifically to edge card connectors in which the connector impedance is controlled by shaping of the connector terminals.

High speed data transfer systems require electrical connectors in which the electrical impedance can be controlled in order to maintain the required data transfer rate of the electrical system. It is desirable at high speed data transfer rates to obtain a specific impedance in a connector that matches the impedance of the entire electronic system, i.e., the circuits on the a circuit board of an electronic device and either the circuits of opposing electronic device or in a transmission cable. The impedance of a connector may be controlled by the spacing of the terminals, the size of the terminals and the thickness and location of material within the connector housing.

However, low profile connectors, such as those used in SFP (Small Form Factor Pluggable) applications are desired in electronic devices in which space is a premium and thus it is difficult to control the impedance by modifying the spacing and size of the terminals in a reduced-size connector housing. When the terminals are modified, it becomes difficult to retain all of the mechanical functions of the connector, such as terminal retention and engagement while tuning the impedance of the connector

The present invention is directed to an improved electrical connector system that combines the aforementioned characteristics.

### **Summary of The Invention**

Accordingly, it is a general object of the present invention to provide a low profile connector in which the terminals may have varying shapes for controlling the impedance of the connector.

Another object of the present invention to provide a surface mount style connector for mounting on a circuit board, the connector having a plurality of conductive terminals supported therein in spaced apart order, the terminals having stubs and slots formed as part thereof, thereby reducing and/or increasing the amount of metal to influence the capacitance and/or the

inductance of the terminals and control the impedance thereof.

A further object of the present invention is to provide a right angle, low profile surface mount connector for use in high speed applications in which the connectors have a specific structure for controlling the impedance and inductance of electrical connectors.

A still further object of the present invention is to provide a connector for surface mounting to a printed circuit board, wherein the connector includes a dielectric housing having first and second opposing mating faces, the first mating face including a plurality of first stamped terminals, the second mating face including a plurality of second stamped terminals the terminals of a first type that are stamped from a metal strip and are inserted into slots in the housing from a front face, and terminals of a second type which are stamped from a second metal strip and are inserted into slots in the housing from a rear face, such that the first and second terminals are offset from each other and wherein the front and rear faces are substantially perpendicular to the printed circuit board onto which the assembly is mounted.

Another object of the present invention is to provide a connector assembly with the aforementioned terminal arrangement, wherein each of the second terminals include a first terminal retention section having a portion removed from the central portion thereof, the first terminal retention section having sufficient metal remaining to retain the terminal in the housing, yet having sufficient surface area to provide a desired capacitance for tuning the impedance of the terminal to the preselected level, the second terminals each having a second terminal retention section with a central portion removed thereof, the removed central portion being spaced away from the first terminal retention area, while minimizing the surface area, size and shape of the central section for tuning the impedance of the terminal to a preselected range.

A further object of this invention is to provide a connector assembly with the aforementioned terminal arrangement and shape, and with a second terminal with a solder section that is used to mount the connector to a printed circuit board, of a size and shape that is used to minimize metal area and the size and shape of the solder portion being used to tune the impedance of the terminal to the specified amount.

The present invention accomplishes the aforementioned and other objects by the way of its novel and unique structure.

In one embodiment of the invention, a connector assembly is provided for mounting to a circuit board with surface mount technology. The connector includes a dielectric housing and terminals of a first type which are stamped from a metal strip and are inserted into slots in a front

face of the connector housing. Terminals of a second type are stamped from a second metal strip and are inserted into slots along the rear face of the connector housing so the first and second type terminals are opposing each other. The first and second sets of terminals are inserted into the connector housing along two distinct faces of the housing, which are preferably on opposite ends of the housing.

The first and second type terminals have cantilevered contact arm portions that extend into an internal receptacle of the connector housing which is designed to receive the edge of a circuit card. At least the second type terminals have contact portions, tail portions and intervening body portions. Part of the second type terminal body portions include terminal retention portions that are press fit into slots formed in the connector housing. At least one of these terminal retention portions has an opening formed therein, which has the practical effect of reducing the surface area of the metal, which affects the capacitance and inductance of the terminal (i.e., lowering the capacitance and increasing the inductance), thereby also influencing the impedance of the connector insofar as adjoining terminals are concerned and the openings are preferably used to tune the impedance of the terminal to a desired level. In order to compensate for the removal of metal in this portion of the terminal, the connector housing is modified to provide additional reaction surfaces that abut the terminal retention portion.

In another embodiment of the invention, the terminals have two terminal retention portions, each of which has an opening formed therein for impedance tuning. In one retention portion, the opening is disposed in a central part of the retention portion and preferably takes the form of a circular opening, while in the other retention portion, the opening takes the form of a slot extending along a central part thereof.

These and other objects, features and advantages of the present invention will be clearly understood through a consideration of the following detailed description.

### **Brief Description of the Drawings**

In the course of this detailed description, the reference will be frequently made to the attached drawings in which:

FIG. 1 is an exploded perspective view of a known connector assembly illustrating one type of circuit board application to which the present invention is directed;

FIG. 2 is a cross-sectional view of the connector assembly of FIG. 1 taken along line 2-2 thereof, removed from the circuit board and illustrating the housing, its mating slot and the

positioning of first and second terminals therein;

FIG. 3 is a cross-sectional view of a connector housing constructed in accordance with the principles of the present invention;

FIG. 4 is a side elevational view of a first type terminal utilized in the connector assembly of FIG. 1 and in the connectors of the present invention;

FIG. 5 is a side elevational view of a second type terminal utilized in connectors of the present invention in which the body portions thereof have been modified to reduce the overall surface area of metal in the body portion and to improve retention of the terminal within the connector housing of FIG. 3;

FIG. 6 is a side elevational view of another embodiment of a second type terminal suitable for use in connectors of the present invention illustrating another modification of only a single terminal body portion to reduce the overall surface area thereof;

FIG. 7 is a perspective view of the connector housing of FIG. 3, angled to show the rear face thereof and having the second terminals of FIG. 5 inserted therein;

FIG. 8 is a cross-sectional view of the connector housing of FIG. 3, with a second terminal as shown in FIG. 6, inserted in place within the rear face of the housing; and,

FIG. 9 is a cross-sectional view of the connector housing of FIG. 3, with a first terminal as shown in FIG. 4 and a second terminal as shown in FIG. 5 inserted therein.

### **Detailed Description of the Preferred Embodiments**

FIG. 1 illustrates a known connector assembly, generally designated as 1, that will be used to explain the environment in which the present invention operates. The connector assembly 1 is a surface-mount style and is intended for mounting to a printed circuit board 2. The connector assembly includes an insulative housing 3, preferably formed from a dielectric material, and a plurality of conductive terminals 19 are supported in the housing 3. The terminals 19 are arranged in two distinct sets of first terminals 4 and second terminals 5. The connector housing preferably has a configuration which includes a plurality of distinct faces and these faces include a first, or front face 6 and an opposing second, or rear face, 7. Side faces or sidewalls 8, 9 are seen to interconnect the front and rear faces 6, 7 of the housing together; and in the embodiment illustrated, the housing. The first face 6 of the connector housing may be considered as a mating face of the connector inasmuch as it contains a slot formed therein for receiving an edge of a circuit board or edge card therein, and the second face 7 of the connector

housing may be considered as a mounting face inasmuch as a portion of the connector, by way of the rear terminals, is mounted to the circuit board 2.

The first terminals 4 are mounted into slots 71 formed in the connector housing 3 along its front face 6, while the second terminals 5 are mounted in slots 72 that are formed in the connector housing 3 along its rear face 7. The front and rear faces 6, 7 are oriented substantially perpendicular to the printed circuit board 2 onto which the connector housing 3 is mounted. Mounting portions 20 formed in the terminals 19 are located on the terminals 19 in locations spaced away from the connector housing 3 and serve as a means for connecting the terminals of the connector to corresponding conductive pads 22 formed with the circuit board 2 in a surface mount manner. These mounting portions are illustrated as conventional surface mount tails. The connector housing 3 may also include mounting pegs, or posts 24 formed therewith that are received within complementary openings 26 formed with the circuit board 2. This Figure depicts the connector environment in which terminals and connectors of the present invention are used.

FIG. 2 illustrates, in cross-section, the connector housing 3 of FIG. 1. This view shows the position of the two sets of terminals 4, 5. The connector housing 3 includes an internal cavity, or receptacle 30, which receives an insertion edge 32 of an edge card 31, illustrated in phantom. The two terminals 4, 5 each have contact arm portions 72, 73 that extend in a cantilevered fashion, from body portions 87, 88, into the internal receptacle 30 along opposite sides thereof in opposition to circuit pads 33 arranged on the circuit card 31. The terminals 4, 5 may also include terminal retention portions 8, 88 & 89 which may or may not form part of the terminal body portions. These retention portions include one or more teeth or barbs, 81, that skive, or cut, into the connector housing material along the edges of the three retention slots 90 which are shown in the Figure.

FIG. 4 illustrates, a first type of terminal 100 that is used in the connectors of the invention. This terminal 100 is seen to have a surface mount portion 22, an elongated, cantilevered contact portion 72 that extends into a card-receiving slot of the connector, a body portion 87, and a terminal retention portion 8 that is received within a slot or cavity formed in the connector housing. Barbs 81 are provided as part of the terminal retention portion 8 to increase the retention of the terminal in the connector housing.

FIG. 5 illustrates a terminal 101 used in the second set (or type) of terminals in connectors of the present invention. The terminal 101 includes an elongated, cantilevered

contact portion 91, a first (upper) retention section 92 that is also considered to be part of a terminal body portion 93. A second (lower) retention section 94 is also provided and is spaced apart from the first retention section 92. Both retention sections 92, 94 are disposed on the terminal 101 between the contact portion 91 and the mounting, or tail portion, 97.

The first retention portion 92 includes a relatively large central part 98, which has an opening 95 formed therein. This opening is shown as circular and completely enclosed within the terminal retention area and serves to reduce the metal of the terminal and this particular portion thereof and it also reduces the capacitance of the terminal with respect to any adjoining terminal, by reducing the amount of surface area of the terminal. This reduction of material also increases the inductance of the terminal, which also influences the impedance of the terminal. The reduction of capacitance (or increase in inductance) will in turn, as is known, affect the impedance of the terminal, and of the connector overall in the region from the second terminal contact portion 91 to the mounting portion 97 thereof. The second terminal retention portion 94 also has an opening 96 formed therein and this opening 96 takes the form of a slot that preferably extends from an edge and through a portion of the central area of the second terminal retention portion 94. This slot 96 is not completely enclosed in the retention portion 94 as in the top retention portion. In the illustrated embodiment, the opening 95 is shown as circular, a variety of other shapes, preferably polygon shapes may be used. The size and shape of this first retention portion 92 may be varied in order to vary the impedance of the system.

FIG. 6 illustrates another embodiment of a second terminal, where the terminal 102 contains a contact section 15, a single retention section 16, and a board mounting section 17. The retention section 16 of this second terminal 102 also contains an opening 18 therein in which metal has been removed from the stamped terminal 102. In the illustrated embodiment, this central portion is substantially circular, but can also take a variety of shapes. The size and shape of this central portion can be varied in order to vary the impedance of the system. The retention section of the second terminal may contain barbs 19 which are used to embed in the slots of the dielectric housing to provide terminal retention. The size of the board mounting portion 17 may also be varied to provide adequate area for mounting to the printed circuit board, while also being tuned to provide a specific impedance in the terminal.

The terminals are easily stamped from sheet metal, but because of the openings 95, 96 formed thereon, a concern is raised about the ability to retain the second terminals 101, 102 within the connector housing 3. This concern is alleviated by modifying the connector housing

3', as illustrated in FIG. 3, in order to provide additional housing material 66', 67' and 68' near the retention slots 90'. The effect of this additional material is shown in FIGS. 8 & 9, where the material 66' and 67' enclose and abut the enlarged terminal first retention portion 92 and in effect, provide additional reaction surfaces against which the retention portions 92, 94 bear. FIG. 9 illustrates how the other second terminal of FIG. 3 is fit into the housings 3' of the invention.

The length and width of the second retention portion can also be varied in order to vary the surface area of the terminal, and therefore also the impedance. Both first and second retention sections of the second terminal may contain barbs, or teeth 51 which are used to embed the terminals 101 firmly and reliably within the slots 72 of the connector housing 3. The size of the board mounting section may also be varied to provide adequate area for mounting to the printed circuit board, while also being tuned to provide a specific impedance in the terminal.

FIG. 7 illustrates the rear face of the connector housing, where each of the terminal receiving slots 72 include a pair of opposing retention bumps 21 disposed on opposite sides of the terminal, for increased terminal retention to the housing.

While the preferred embodiment of the invention have been shown and described, it will be apparent to those skilled in the art that changes and modifications may be made therein without departing from the spirit of the invention, the scope of which is defined by the appended claims.



**CLAIMS:**

1. A connector for providing a connection between a circuit board and an opposing electronic element, the circuit board having a plurality of conductive traces disposed thereon and the opposing electronic element including a male portion having a plurality of conductive members disposed thereon, comprising:
  - an insulative connector housing having first and second ends interconnected by an intervening body portion, the first end being a mating end including a receptacle portion for mating with said opposing electronic element and the second end being a mounting end for mounting said connector housing to said circuit board;
  - a plurality of conductive terminals supported by said housing, the terminals being arranged in distinct sets of first and second terminals, the first and second terminals including contact portions for contacting a corresponding conductive member of said opposing electronic element, mountings portion for mounting said terminal to a circuit board, body portions interconnecting the terminal contact and mounting portions together, and retention portions for retaining the terminal in place with the connector housing, the terminal retention portions being disposed intermediate said terminal contact and terminal mounting portions; and,
  - said retention portions of the second terminals having openings disposed therein, the openings being centrally located within said terminal retention portions and being of sufficient size so as not to weaken the retention of said second terminals within said connector housing by said terminal retention portions.
2. The connector as claimed in claim 1, wherein said connector housing includes a plurality of first and second cavities, each of the first cavities receiving a single first terminal therein and each of the second cavities receiving a single second terminal therein.
3. The connector as claimed in claim 2, wherein each of said second cavities includes a step formed therein, the steps being aligned with opposing terminal retention portions of said second terminals disposed within said second cavities.
4. The connector as claimed in claim 1, wherein said openings include circular openings.

5. The connector as claimed in claim 1, wherein openings include slots.
6. The connector as claimed in claim 1, wherein said second terminals include two distinct retention portions spaced apart from each other, one terminal retention portion being disposed proximate to said terminal contact portion and the other terminal retention portion being disposed proximate to said terminal mounting portion, each of said two terminal retention portions including openings formed therein, one of said openings including a slot.
7. The connector as claimed in claim 5, wherein said terminal retention portion slots extend lengthwise within said connector housing.
8. The connector as claimed in claim 6, wherein said one terminal retention portion includes an opening that is enclosed within said one terminal retention portion and said other terminal retention portion includes a linear slot, and said one terminal retention portion is disposed above said other terminal retention portion.
9. The connector as claimed in claim 3, wherein some of said steps extend toward said terminal contact portions.
10. The connector as claimed in claim 1, wherein said second cavities include a plurality of projections that extend inwardly from opposite sides of said second cavities into contact with said second terminals proximate to said terminal mounting portions thereof to stabilize said second terminals in said second cavities.,

## AMENDED CLAIMS

[received by the International Bureau on 12 September 2003 (12.07.2003)  
original claims 1-10 replaced by amended claims 1-9]


**CLAIMS:**

1. A connector (1) for providing a connection between a circuit board (2) and an opposing electronic element, the circuit board (2) having a plurality of conductive traces (22) disposed thereon and the opposing electronic element including a male portion having a plurality of conductive members disposed thereon, comprising:
  - an insulative connector housing (3) having first (6) and second (7) ends interconnected by an intervening side walls (8, 9), the first end (6) being a mating end including a receptacle portion (30) for mating with said opposing electronic element and the second end (7) being a mounting end for mounting said connector housing (3) to said circuit board(2);
  - a plurality of conductive terminals (19) supported by said housing (3), the terminals (19) being arranged in distinct sets of first (4) and second (5) terminals, the first (4) and second (5) terminals including contact portions (72, 91) for contacting a corresponding conductive member of said opposing electronic element, mountings posts (24) for mounting said terminals (19) to a circuit board (2), body portions (87, 93) interconnecting the terminal contact (72, 91) and mounting portions (22, 97) together, and retention portions (8, 92, 94) for retaining the terminal in place with the connector housing (3), the terminal retention portions (8, 92, 94) being disposed intermediate said terminal contact (72, 91) and terminal mounting portions (22, 97); characterized in that:
    - each of said second terminals (5) include two distinct retention portions (92, 94) spaced apart from each other, one terminal retention portion (92) being disposed proximate to said second terminal contact portion (91) and the other terminal retention portion (94) being disposed proximate to said second terminal mounting portion (97), each of said two terminal retention portions (92, 94) further including respective first and second openings (95, 96) centrally disposed within said upper and lower terminal retention portions (92, 94), said openings being sized so as not to weaken the retention of said second terminals (101) within said connector housing (3) by said terminal retention portions (92, 94) and said openings reducing capacitive coupling between adjacent first and second terminals by reducing surface area of said second terminals in said upper and lower retention portions.
2. The connector (1) as claimed in claim 1, wherein said connector housing (3) includes a

plurality of first and second slots (71), each of the first slots (71) receiving a single first terminal (4) therein and each of the second slots (71) receiving a single second terminal (5) therein.

3. The connector (1) as claimed in claim 2, wherein each of said second slots (71) includes a step (66, 67, 68) formed therein, the steps (66, 67, 68) being aligned with opposing terminal retention portions (92, 94) of said second terminals (102) disposed within said second cavities.
4. The connector (1) as claimed in claim 1, wherein said openings (95, 96) include circular openings.
5. The connector (1) as claimed in claim 1, wherein said openings (95, 96) include slots (71).
6. The connector (1) as claimed in claim 5, wherein said terminal retention portion (94) slots (71) extend lengthwise within said connector housing (3).
7. The connector (1) as claimed in claim 1, wherein said one terminal retention portion (92) includes first opening (95) that is enclosed within said one terminal retention portion (92) and said other terminal retention portion (94) includes a linear slot (96), and said one terminal retention portion (92) is disposed above said other terminal retention portion (94) the linear slot (96) being open at one end and having a central axis that is substantially orthogonal to a line that is orthogonal to the first opening (95).
8. The connector (1) as claimed in claim 3, wherein some of said steps (66, 67, 68) extend toward said terminal contact portions (91).
9. The connector (1) as claimed in claim 2, wherein said second slots (71) include a plurality of projections (68) that extend inwardly from opposite sides of said second slots (71) into contact with said second terminals (5) proximate to said terminal mounting portions (97) thereof to stabilize said second terminals (5) in said second slots (71).


**FIG. 1**  
(PRIOR ART)






**FIG. 4**

3/4



**FIG. 5**



**FIG. 6**




FIG. 7

4/4




FIG. 8





FIG. 9





## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 03/14410

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H01R12/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 356 156 A (MOLEX INC) 28 February 1990 (1990-02-28) column 8, line 44 - line 58	1-10
X	EP 0 651 470 A (FRAMATOME CONNECTORS INT) 3 May 1995 (1995-05-03) column 4, line 2 - line 25	1-4, 9, 10
A	US 5 309 630 A (BRUNKER DAVID L ET AL) 10 May 1994 (1994-05-10)	

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the International filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the International filing date but later than the priority date claimed

\*T\* later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the International search

3 July 2003

Date of mailing of the international search report

11/07/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Bertin, M

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International Application No  
**PCT/US 03/14410**

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0356156	A	28-02-1990	US 4891023 A	02-01-1990
			DE 68921117 D1	23-03-1995
			DE 68921117 T2	28-09-1995
			EP 0356156 A2	28-02-1990
			JP 1809045 C	10-12-1993
			JP 2114477 A	26-04-1990
			JP 5006315 B	26-01-1993
EP 0651470	A	03-05-1995	US 5425658 A	20-06-1995
			DE 69417988 D1	27-05-1999
			DE 69417988 T2	16-09-1999
			EP 0651470 A2	03-05-1995
US 5309630	A	10-05-1994	US 5203725 A	20-04-1993
			US 5713764 A	03-02-1998
			US 5921815 A	13-07-1999
			DE 69311169 D1	10-07-1997
			DE 69311169 T2	08-01-1998
			EP 0561288 A1	22-09-1993
			ES 2103993 T3	01-10-1997
			JP 2835563 B2	14-12-1998
			JP 6060947 A	04-03-1994
			KR 173629 Y1	02-03-2000
			SG 44612 A1	19-12-1997
			DE 69325198 D1	15-07-1999
			DE 69325198 T2	09-03-2000
			EP 0562427 A2	29-09-1993
			EP 0892470 A2	20-01-1999
			ES 2133337 T3	16-09-1999
			JP 1986190 C	08-11-1995
			JP 6096814 A	08-04-1994
			JP 6105628 B	21-12-1994
			KR 9701949 B1	19-02-1997
			SG 47051 A1	20-03-1998
			US 5522737 A	04-06-1996
			US 5259768 A	09-11-1993
			US 6019639 A	01-02-2000
			US 5853303 A	29-12-1998